



| Model                       | Superlift LX2024 A17 |
|-----------------------------|----------------------|
| Capacity                    | 2300kg               |
| Platform dimensions (L x W) | 1.70m x 1.40m        |
| Max lifting height          | 200m                 |
| Speed                       | 24m/min              |
| Height of mast section      | 1.5m                 |
| Weight of mast section      | 140kg / 165kg        |
| Tie spacing (Max)           | 15m                  |
| Mast top                    | 9m                   |
| Motor capacity              | 2x 7.5kW             |
| Rated supply required       | 32 Amp / 63 Amp      |
| Electrical supply (V/Hz)    | 415 / 3 / 50         |
| Control voltage (V)         | 230                  |

## Summary

The Bocker LX2024 A17 is a robust and versatile hoist and can be configured to carry materials only, with a total capacity of up to 2300kg.

With the options for both single or twin cage operation, along with C gate options available, the LX2024 is highly versatile and can be adapted to suit virtually any site's needs. The compact space-saving design allows for a total of 1.70m x 1.40m of floor space.

## Product Advantages

- Mast compatible with Giant Lift hoist for a combination hoist
- Variable ties interface directly with the building or scaffold
- Economic automatic control, no manual switching
- Mechanical and electrical locking mechanisms
- Single or Twin cage operation
- Operating height of up to 200m
- Up to 15m vertical tie spacings
- Automated lubrication system
- Flexible modular construction
- Operating speed of 24m/min
- C Gate options also available
- Scaffold Carrier option available

