



Model	Superlift LX2024 A25
Capacity	2000kg
Platform dimensions (L x W)	2.55m x 1.40m
Max lifting height	200m
Speed	24m/min
Height of mast section	1.5m
Weight of mast section	140kg / 165kg
Tie spacing (Max)	15m
Mast top	9m
Motor capacity	2x 7.5kW
Rated supply required	32 Amp / 63 Amp
Electrical supply (V/Hz)	415 / 3 / 50
Control voltage (V)	230

Summary

The Bocker LX2024 A25 is a robust and versatile hoist and can be configured to carry materials only, with a total capacity of up to 2000kg.

With the options for both single or twin cage operation, along with C gate options available, the LX2024 is highly versatile and can be adapted to suit virtually any site's needs. The compact space-saving design allows for a total of 2.55m x 1.40m of floor space.

Product Advantages

- Mast compatible with Giant Lift hoist for a combination hoist
- Variable ties interface directly with the building or scaffold
- Economic automatic control, no manual switching
- Mechanical and electrical locking mechanisms
- Single or Twin cage operation
- Operating height of up to 200m
- Up to 15m vertical tie spacings
- Automated lubrication system
- Flexible modular construction
- Operating speed of 24m/min
- C Gate options also available
- Scaffold Carrier option available

