



Model	Superlift MX320
Capacity	300kg
Platform dimensions (L x W)	1.40m x 0.85m
Max lifting height	100m
Speed	20m/min
Height of mast section	2.0m
Weight of mast section	20kg
Tie spacing (Max)	4m
Mast top	1m
Motor capacity	1.8kW
Rated supply required	16 Amp
Electrical supply (V/Hz)	415 / 3 / 50
Control voltage (V)	42

Summary

The Bocker MX320 is a robust and versatile hoist. Easily manoeuvred on its wheeled chassis, it can be positioned just about anywhere on the tightest of sites and can carry loads of up to 300kg.

Specially designed Carriers are available (optional) to safely transport scaffold tubes & boards, plasterboard, roofing materials and sheets. It's compact, space-saving design with a platform offers 1.40m x 0.85m of floor space within the hoist.

Product Advantages

- Reduced Power Consumption*
- Mast design for reduced tie and base loading
- Operating speed of 20m/min
- Operating height of up to 100m
- Ease of operation with dual control system
- Flexible modular construction
- Mechanical and electrical locking mechanisms
- Robust construction & fully galvanised
- Payload of 300kg (evenly distributed)
- Easily manoeuvred into position on wheeled chassis.
- Scaffold Carrier option available

Single Configuration

