

## ➤ Bocker Superlift Z320



Model	Superlift Z320
Capacity	300kg
Platform dimensions (L x W)	1.40m x 0.85m
Max lifting height	50m
Speed	20m/min
Height of mast section	2.0m
Weight of mast section	29kg
Tie spacing (Max)	4m
Mast top	3m
Motor capacity	1.7kW
Rated supply required	16 Amp
Electrical supply (V/Hz)	230 / 1 / 50
Control voltage (V)	42

### Summary

The Bocker Z320 is a robust and versatile hoist. Easily manoeuvred on its wheeled chassis, it can be positioned just about anywhere on the tightest of sites and can carry loads of up to 300kg.

Specially designed carriers are available (optional) to safely transport scaffold tubes & board, plasterboard, roofing materials and sheets. It's compact, space-saving design using a swivel platform offers 1.40m x 0.80m of floor space within the hoist.

### Product Advantages

- Reduced power consumption\*
- Operating height of up to 50m
- Ease of operation with control pendant
- Flexible modular construction
- Space saving compact swivel design
- Mast designed for reduced tie and base loading
- Operating speed of 20m/min
- Mechanical and electrical locking mechanisms
- Robust construction & fully galvanised
- Payload of 300kg (evenly distributed)
- Easily manoeuvred into position on wheeled chassis
- Scaffold Carrier option available

Single Configuration

